
Zinc Oxide 70% Zn Feed





Parameter	Unity	Guarantee
Purity (ZnO)	%	87,13 min
Purity (Zn)	%	70,00 min
Humidity at 100°C	%	1,00 max
Iron	%	According to agreement.
Lead	%	According to agreement.
Mesh 18	%	99,00 min



Presentation

Sacks of microperforated laminated polypropylene of 25 kg net weight.

We can provide more presentations of our products as packaging in Big Bags of 500 Kg and 1000 Kg.

Uses and Applications

In animal nutrition as a source of zinc, in agriculture in compound fertilizers and as a source of zinc in the manufacture of derivatives such as: sulfates, chlorides, nitrates, etc.

© Industrias emu s.a.s. | Soluciones Agro-Industriales | Colombia

Medellín, ITAGÜÍ: Carrera 41 No. 46 - 132 - Itagüí, Antioquia, Colombia

+57 (4) 373 1112 | +57 314 700 5761

Bogotá, COTA: Calle 80, Km 1.5 Via Siberia, Bodega 01 Local 51, Parque Agroindustrial del

Occidente - Cota, Cundinamarca, Colombia +57 (4) 373 1112 Ext 301 | +57 314 773 4473

Barranquilla, SOLEDAD: Calle 30 No. 13 - 278, Km.7 Via Aeropuerto - Soledad, Atlántico, Colombia +57 (5) 343 6822 | +57 317 441 3758

www.industriasemu.com