

Zinc Oxide White Seal



Formula	ZnO
Molecular Weight	81,38 g/mol
Appearance	Dust
Color	White

Parameter	Unity	Guarantee
Purity (ZnO)	%	99,58 min
Purity (Zn)	%	80,00 min
Humidity at 100°C	%	0,20 max
Lead	%	According to agreement.
Iron	%	According to agreement.
Mesh Size 325	%	99.5 min

Presentation

Sacks of microperforated laminated polypropylene of 25 kg net weight.

We can provide more presentations of our products as packaging in Big Bags of 500 Kg and 1000 Kg.

Uses and Applications

Pigment activator and accelerator and reinforcing agent in rubber and high polymers, rubber vulcanization processes, paints, ceramics, zinc salts, food additives, seed treatment, photoconductor in copying machines, animal feed additives, etc.



© Industrias emu s.a.s. | Soluciones Agro-Industriales | Colombia

Medellín, ITAGÜÍ: Carrera 41 No. 46 - 132 - Itagüí, Antioquia, Colombia
+57 (4) 373 1112 | +57 314 700 5761

Bogotá, COTA: Calle 80, Km 1.5 Via Siberia, Bodega 01 Local 51, Parque Agroindustrial del Occidente - Cota, Cundinamarca, Colombia
+57 (4) 373 1112 Ext 301 | +57 314 773 4473

Barranquilla, SOLEDAD: Calle 30 No. 13 - 278, Km.7 Via Aeropuerto - Soledad, Atlántico, Colombia
+57 (5) 343 6822 | +57 317 441 3758